




BT50-SA1022-III



型号	L	φC	KG	丝锥尺寸	丝锥筒夹
BT30-SA 206-III	120	33	0.6	M 2~8	TC 206
-SA 412-III	150	48	1.1	M 3~16	TC 412
BT40-SA 206-III	120	33	1.2	M 2~8	TC 206
-SA 412-III	150	48	1.7	M 3~16	TC 412
-SA1022-III	195	66	2.7	M 8~27	TC1022
-SA2035-III	240	84	3.9	M18~38	TC2035
BT50-SA 206-III	150	33	4	M 2~8	TC 206
-SA 412-III		48	4.2	M 3~16	TC 412
-SA1022-III	195	66	5	M 8~27	TC1022
-SA2035-III	225	84	5.8	M18~38	TC2035
-SA3050-III	285	104	8.6	M27~56	TC3050
A63 -SA 206-III	150	33	1.4	M 2~8	TC 206
-SA 412-III	165	48	1.7	M 3~16	TC 412
-SA1022-III	225	66	2.8	M 8~27	TC1022

关于丝锥筒夹

除标准品外, 另有可调整扭矩产品。

1. 扭矩降低型 (黄筒夹)

针对铝件轻合金等软材的攻牙, 也备有降低扭矩的丝锥套筒请在编码后附加

"-黄"字样。

(订购例: TC412-M4-黄)

2. 提高扭矩型 (红筒夹)


针对不锈钢, 特殊钢等难切削材的加工, 备有提高扭矩的丝锥套筒。请在编码末尾后附加"-红"字样。

(订购例: TC1022-M8-红)

■选购品

- 丝锥筒夹 ●拉钉(BT)→P.77

丝锥筒夹



M=公制螺纹
U=统一标准螺纹
P=管螺纹

■选购品

●备有去除了自动安全装置的MO型产品。详情请垂询弊司。

型号	D			H	φC ₁	φC ₂
	M	U	P			
TC206 -M 2	2	#2,3,4	-	21	21	15
-M 3	3	#5, 6				
-M 4	4	#8				
-M 5	5	#10,12				
-M 6	6	1/4				
-M 8	8	-				
TC412 -M 3	3	#5, 6	-	20.5	33	20
-M 4	4	#8				
-M 5	5	#10,12				
-M 6	6	1/4				
-U 5/16	-	5/16				
-M 8	8	-				
-M10	10	3/8				
- 1/8 P	11	7/16	1/8			
-M12	12	-				
-U 1/2	-	1/2				
-M14	14	9/16		33		27
-M16	16	-				
TC1022-M 8	8	-	-	39.5	50	32
-U 7/16	11	7/16				
-M12	12	-				
-U 1/2	-	1/2				
-M14	14	9/16				
-U 5/8	-	5/8				

型号	D			H	φC ₁	φC ₂
	M	U	P			
TC1022-M16	16	-	-	39.5	50	32
-M18	18	3/4				
-M20	20	-				
-M22	22	7/8				
-M24	24	-		45.5	50	36
-M27	27	1				
- 1/8 P	-	-	1/8	32	50	32
- 1/4 P			1/4			
- 3/8 P			3/8			
- 1/2 P			1/2			
- 5/8 P			5/8			
TC2035-M18	18	3/4	-	53.5	70	46
-M20	20	-				
-M22	22	7/8				
-M24	24	-				
-M27	27	1				
-M28	28	-				
-U 1 1/8	-	1 1/8				
-M30	30	-				
-M32	32	1 1/4				
-M33	33	-				
-M35	35	1 3/8				
-M36	36	-				

型号	D			H	φC ₁	φC ₂
	M	U	P			
TC2035- 1/2 P	-	-	1/2	38.5	70	46
- 5/8 P			5/8			
- 3/4 P			3/4			
- 7/8 P			7/8			
- 1P			1			
TC3050-M27	27	1	-	47.5	87	64
-M28	28	-				
-M30	30			63.5		
-M32	32	1 1/4				
-M33	33	-				
-M35	35	1 3/8				
-M36	36	-				
-M39	39	1 1/2				
-M42	42	1 5/8				
-M45	45	1 3/4				
-M48	48	-				
-M50	50	2				
-M52	52	-				
-M56	56	2 1/4		71.5		68
- 3/4 P	-	-	3/4	48	85	64
- 7/8 P			7/8			
- 1P			1			
- 1 1/8 P			1 1/8			
- 1 1/4 P			1 1/4			
- 1 1/2 P			1 1/2			
- 1 3/4 P			1 3/4			